

## **PG325 PORTABLE GENERATOR**

|                                     | PG325                        |
|-------------------------------------|------------------------------|
| PRIME POWER RATING                  |                              |
| @ 480V-3Ø, 0.8PF, 60Hz              | 334 kVA   267 kW   401 A     |
| @ 240V-3Ø, 0.8PF, 60Hz              | 334 kVA   267 kW   803 A     |
| @ 208V-3Ø, 0.8PF, 60Hz              | 316 kVA   253 kW   877 A     |
| @ 240V-1Ø, 1.0PF, 60Hz              | 197 kVA   197 kW   821 A     |
| @ 120V-1Ø, 1.0PF, 60Hz              | 197 kVA   197 kW   821 × 2 A |
| @ 400V-3Ø, 0.8PF, 50Hz              | 280 kVA   224 kW   404 A     |
| Voltage Configuration               | Link Board Panel             |
| Frequency Capability                | 50 Hz/60 Hz Switchable       |
| ENGINE                              |                              |
| Make & Model                        | Cummins QSL9-G9              |
| Displacement                        | 8.9 L                        |
| Number of Cylinders                 | 6                            |
| Power Output @ 1800 rpm             | 393 hp (293 kWm)             |
| Emissions Tier Level                | Tier 4 Final                 |
| Aftertreatment Technology           | DOC / SCR                    |
| Usable Fuel Tank Capacity           | 480 gal. (1817 L)            |
| Diesel Exhaust Fluid (DEF) Capacity | 24 gal. (91 L)               |
| Runtime @ 75% Load                  | 33 hr.                       |
| DIMENSIONS WITH RUNNING GEAR        |                              |
| Length                              | 240.0 in. (6098 mm)          |
| Width                               | 83.0 in. (2109 mm)           |
| Height                              | 113.0 in. (2870 mm)          |
| Weight (Ready to Run)               | 14,032 lb. (6378 kg)         |
| Sound Level @ 23 ft. (7 m) and 100% | 76 dB(A)                     |

## **KEY FEATURES**

Powered by a Cummins QSL9-G9 engine, the Bobcat® PG325 portable generator offers heavy-duty power capable of operating in extreme conditions.

- This generator delivers an impressive output of 334 kVA/267 kW while maintaining a quiet noise level of just 76 dB(A), ensuring powerful performance with minimal noise disturbance.
- Even under a 100% load, this generator provides a continuous 24-hour runtime for reliable power supply for extended periods of operation.
- Enjoy an easy-to-read analog control panel for quick and effortless monitoring.
- The connection panel is conveniently accessible, prioritizing safety for smoother operations.
- Optional paralleling controller provides parallel connectivity and efficiency to meet expanded power needs.



Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.



The images shown are for illustration purposes only and may not be an exact representation of the product

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries.

